

Modular luminaire Clean room 60x60 4000K

REF. 75501330-394



BASIC INFORMATION

DESCRIPTION

Sealed LED luminaire 755 (595x595mm) with multilayer front (microprismatic diffuser + tempered glass) for demanding environments. CRI90, 4000K, UGR<19. DALI-2 driver with energy report and diagnostics. IP65, IK08. Power 45W, output 4900lm, efficiency 109 lm/W. Perfect for hospitals, labs, clean rooms. Complies with UNE EN ISO 14644 Class 1.

FINISH

White

APPLICATION

Healthcare

MATERIAL

Aluminium

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

08

IP RATING

IP65

OPERATING TEMPERATURE RANGE (°C)

-20...+35

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI2

COLOR TYPE

NW

OPTICS

Diffused

REGULATIONS

REGULATIONS

Dir. 2014/30/UE EMC | Dir. 2014/35/UE LVD | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2011/65/UE RoHS + post. mod | EN IEC 60598-2-2:2023 used in conjunction IEC 60598-1:2020 | EN IEC 55015:2019 + A11:2020 | EN 60598-2-25:1994 + A1:2004 | EN IEC 61547:2023 | EN 62493:2015 | EN IEC 61000-3-2:2019 + A1:2021*1 | EN 62717:2017 + A2:2019 | EN 61000-3-3:2013 + A1:2019 + A2:2021 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053360064

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

9.2

PRODUCT NET WEIGHT

8.6

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053360064

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

110

PACKAGING WIDTH

600

PACKAGING LENGTH

600

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

39600000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

9.5

PACKAGING NET WEIGHT

8.6

PACKAGING WEIGHT UNIT

KGM