


Flush-mount trim cover for adjustable floor box or service cover 12 elements grey Simon 500 Cima

REF. 52053106-035



BASIC INFORMATION

DESCRIPTION

Flush-mount trim cover for adjustable floor box or service cover in grey finish, this cover belongs to one of the collections that are dedicated to the most outstanding advancement in the workplace solutions for work stations: The Simon 500 Cima series. The dimensions that has this trim cover are 282 x 156 x 5 millimetres. As an optional element, it is possible to combine with the floor box if not installing the same floor lining type. All the products in the Simon 500 Cima series are made of halogen-free thermoplastic, thus guaranteeing no flame propagation in case of fire and low toxicity in the promoting to send fumes contaminants. To clean, use a soft, dry cloth, never use cloths or abrasive cleaners that have chlorine among its components.

FINISH

Grey

PACKAGING CONTENTS

Trim cover

MATERIAL

Plastic

ETIM CLASS

EC002417

REMARKS

Optional element. To combine with the floor box if not installing the same floor finish.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IK CLASSIFICATION

08

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

AVAILABLE IN

2, 4, 6, 8 and 12 elements

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

NUMBER OF MODULES

12 modules

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

IP RATING

IP4X

RAL

7011

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

KIT AVAILABILITY

No

VERSION

12 elements

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using the screws supplied

INSTALLATION TYPE

In raised or concrete floor with adjustable floor boxes or service covers

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

INSTALLATION DIRECTION

Horizontal, Vertical

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053101568

PACKAGING VOLUME
7.483

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
75

PACKAGING GROSS WEIGHT
0

UNITARY PACKAGING GROSS
WEIGHT
0.202

PACKAGING WIDTH
165

PACKAGING NET WEIGHT
2.02

PRODUCT NET WEIGHT
0.202

PACKAGING LENGTH
290

PACKAGING WEIGHT UNIT
KGM

