

Wire outlet mechanism with 4 double terminals and fixing cable tie white Simon 31

REF. 31801-30



BASIC INFORMATION

DESCRIPTION

The Brand Simon, always looking for the classic lines and pure lines, has created the range Simon 31. This line defines the clarity and convenience of the electric mechanism. With a simple assembly, this series single require mechanism that includes the corresponding cover or rocker, and the frame. This makes it an easy series to install and at the same time with unsurpassed quality and durability, as we at Simon are accustomed to. Simon 31 adapts to different environments according to its colour: For those who prefer the colours of always and not want to risk the colour, white and ivory, it adapts to any option of design and for any project. Simon 31, a series of great creditworthiness prepared for any need of centralization. Other Mechanisms: It is a wire outlet with 4 double terminals connection and cable tie. Colour, Simon 31 white range. Consumption 380 V ~. screw terminal connection. For wire section up to 2.5 mm Single Output of 1 element and 2 modules. Supports 1.5 to 2.5 mm stripped wire up to 7 mm. Resistant to extreme temperatures: 5 to 40° C and -25 to 50° C. Strict standards regarding connections and safety of components. Metal components with halogen-free insulation and thermoplastic trim.

FINISH

White

PACKAGING CONTENTS

Wire outlet mechanism

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC000011

REMARKS

For wire section up to 2.5 mm

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

No

POWER SUPPLY (V~)

380 V~

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

NUMBER OF CONTACTS

4

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

NUMBER OF CONTROLLABLE CIRCUITS

2

NUMBER OF WIRES

4

NUMBER OF POSSIBLE ELEMENTS

1 element

OPERATING TEMPERATURE

RANGE (°C)

5 - 40 °C

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

7

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

UNE-EN 60998-1:2005

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053006535

PACKAGING VOLUME
3409560

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
82

PACKAGING GROSS WEIGHT
0.81

UNITARY PACKAGING GROSS
WEIGHT
0.081

PACKAGING WIDTH
165

PACKAGING NET WEIGHT
0.81

PRODUCT NET WEIGHT
0.081

PACKAGING LENGTH
252

PACKAGING WEIGHT UNIT
KGM