

Brightness sensor recessed box KNX round white IP20

REF. 89262720-130



BASIC INFORMATION

DESCRIPTION

Built-in light detector. The recommended installation height is 2.8 m, with a maximum height of 4 m. The light regulation range is 2 - 1000 lux. The detector configuration is carried out via remote control and KNX. It has a TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The power supply voltage is KNX (21 - 30 VDC). The operating temperature of the detector is: -20 - 50 °C. Black finish, IP 54 protection rating, and dimensions: Ø 124 x 51 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000927

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9003

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.3

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053401620

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.215

PRODUCT NET WEIGHT

0.125

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053401620

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

124

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.215

PACKAGING NET WEIGHT

0.125

PACKAGING WEIGHT UNIT

KGM