Voice and data angled plate for 1 element without dust cover for 1 RJ45 connector black Simon K45

REF. **K080/14**



BASIC INFORMATION

DESCRIPTION

The Simon K45 range, with flat or angled plates, offers maximum safety with its protected opening system, and total Compatibility Guarantee with voice and data connectors on the market in both copper (RJ45) and Fibre Optics. The safety of people is guaranteed since the materials are free of halogens and are fireproof. They are also resistant to corrosion, overloading and to extreme changes in temperature. Connectors and plates for voice and data connections. This is an angled voice and data plate without dust cover with 1 element for 1 RJ45 connector Simon K45 black. Compatible with RJ45 connector. Suitable for combined MD module. black finish. Plate for 1 and 2 RJ45 connectors. When combining the voice and data plate in vertical housing (mini columns, columns, Teleblock, mechanism holder trunking) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position. Dimensions 45 x 45 mm

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Angled voice and data plate without dust cover

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

IP RATING
IP20

RAL
7021

RJ45 CONNECTORS
Not included in voice and data plate

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RJ45 ADAPTOR MODULE
Not included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

SNAP-FIT RJ45 PLATES
According to combined MD module

DUST PROTECTION
No

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

SNAP-FIT TYPE
According to combined MD module

FORMAT
RJ45

NUMBER OF MODULES
Half

VERSION
Single

PLATE TYPE
Angled

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
88

UNITARY PACKAGING WIDTH
123

UNITARY PACKAGING LENGTH
136

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
1472064

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.012

PRODUCT NET WEIGHT
0.012

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436037861

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
88

PACKAGING WIDTH
123

PACKAGING LENGTH
136

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1.472

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.24

PACKAGING NET WEIGHT
0.24

PACKAGING WEIGHT UNIT
KGM