

# Luminaire HOLE 50 Flush mount 2700K Flood Orange CRI98

REF. 91411932-203



## BASIC INFORMATION

### FINISH

Orange

### APPLICATION

Flush mount

### PACKAGING CONTENTS

1 unit

### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CRI

90

### LUMENS (LM)

700 lm

### IP RATING

IP20

### DRIVER INCLUDED

No

### LUMENS/W

700

### OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

### ELECTRICAL CLASS

Type 3

### MACADAM STEPS

<3 Step MacAdam

### POWER SUPPLY (V~)

33 V~

### L70 (°C)

150.000h at 25°C

### OPTICS

Flood 35°

### COLOR TEMPERATURE (K)

4000 K

### L90 (°C)

40.000h at 25°C

### POWER (W)

9 W

### LIGHTING EFFICIENCY (LM/W)

103 lm/W

### SERVICE LIFE

50.000 h

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Flush mount

## REGULATIONS

### EAC MARKED

Yes

### WARRANTY

5 years

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT  
0

UNITARY PACKAGING WEIGHT  
UNIT  
KGM

PACKAGING MEASUREMENT  
UNIT  
MMT

UNITARY PACKAGING WIDTH  
0

PACKAGING EAN  
8421053221297

PACKAGING VOLUME  
4083200

UNITARY PACKAGING LENGTH  
0

UNITS CONTAINED PACKAGING  
1

PACKAGING VOLUME UNIT  
MMQ

UNITARY PACKAGING VOLUME  
0

PACKAGING HEIGHT  
80

PACKAGING GROSS WEIGHT  
0.432

UNITARY PACKAGING GROSS  
WEIGHT  
0

PACKAGING WIDTH  
176

PACKAGING NET WEIGHT  
0.432

PRODUCT NET WEIGHT  
0.432

PACKAGING LENGTH  
290

PACKAGING WEIGHT UNIT  
KGM