

VGA HD15 female connector with trim plate black Simon K45

REF. K100A/14



BASIC INFORMATION

DESCRIPTION

For VGA HD15 female connector with black trim plate in colour, the mechanism is part of the series Simon K45. Allows a welding terminal connection and is suitable for surface and flush mounting. It is composed of metal parts with thermoplastic insulation and self-extinguishing halogen-free. It is a material very safe in case of fire, as it guarantees no flame spread in case of fire and the low toxicity if there is smoke. It measures 22.5x45 mm and is characterized by an extraordinary resistance to extreme temperatures, the ideal, however, is to install it in environments ranging between 5 and 40°. The maximum recommended length of the cabling is 20 meters, for more information, please refer to the product instruction sheet. When it comes to maintenance, you can use a soft, dry cloth for optimum preservation.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

VGA HD15 female connector

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 20 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

CONNECTOR TYPE

VGA

NUMBER OF WIRES

10

NUMBER OF CONTACTS

15

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1/2 element

RAL

7021

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45
and specific Simon 500 Cima
using adaptor (ref.50012088-
038)

INSTALLATION TYPE

Suitable for surface and flush
mounting

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
70

UNITARY PACKAGING WIDTH
93

UNITARY PACKAGING LENGTH
140

UNITARY PACKAGING
MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
911.4

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.016

PRODUCT NET WEIGHT
0.016

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8426436045453

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
911.4

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.16

PACKAGING NET WEIGHT
0.16

PACKAGING WEIGHT UNIT
KGM