Industrial luminaire 816.43 5000K GN DALI

REF. **81643338-785**

BASIC INFORMATION

APPLICATION

Accent lighting,General lighting

ETIM CLASS

EC001716

TECHNICAL INFORMATION

IK CLASSIFICATION
08

IP RATING
IP65

COLOR TEMPERATURE (K)
5000 K

CONTROL
On/Off

CRI
80

L70 (°C)
50.000 h at 25°C

LIGHT BEAM APERTURE ANGLE (°)
90°

LIGHTING EFFICIENCY (LM/W)
137 lm/W

LUMENS (LM)
27400 lm

LUMENS/W
27400 lm / 200W

OPTICS
General

PHOTOBIOLOGICAL CLASSIFICATION
Exempt category

POWER (W)
200 W

SERVICE LIFE
50.000 h

CHROMATICS CRI ICONS

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Discontinued

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053229330

UNITARY PACKAGING HEIGHT
190

UNITARY PACKAGING WIDTH
420

UNITARY PACKAGING LENGTH
420

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
33516000

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
5.9

PRODUCT NET WEIGHT
4.8

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053229330

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
190

PACKAGING WIDTH
420

PACKAGING LENGTH
420

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
33516000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
5.9

PACKAGING NET WEIGHT
4.8

PACKAGING WEIGHT UNIT
KGM