

Complete kit with dual opening cover, brushes, 4xUSB charger and 6 schuko socket outlets black S400 Indesk Duo

REF. 46423000-138



BASIC INFORMATION

DESCRIPTION

Particular and professional users are already enjoying all the advantages of having the complete kit integrated into the table with two openings, brushes, a 4xUSB charger, and six black schuko socket bases from the Simon 400 Indesk Duo series, a range whose functions complement its installation, which is suitable for flush mounting in furniture. This product features a Wieland® gst18i figure connector with three aerial male poles and a 22 cm patch cord, an insulation resistance of >5 MO at 500 V, and dielectric strength without perforation or contortion at 2000 V at 50 Hz for 1 minute. It has a current of 16 A and a voltage of 250 V~. Additionally, it has been designed with a painted steel enclosure, anodized aluminum profile, lids, and fastenings made of self-extinguishing thermoplastic and halogen-free materials, which prevent flame propagation in case of fire and low toxicity in case of smoke emission.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ a 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

TYPE OF POWER SUPPLY CONNECTOR

Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9005

RECESS DIMENSION (MM)

228 x 175 mm (± 2mm)

NUMBER OF SOCKETS

6 sockets for standard current circuit

NUMBER OF USB CHARGERS

2

VERSION

8 elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With brush

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure. Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45° and 135°

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2014/30/UE EMC;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;EN 60950-1:2006;EN 60950-1:2006 A11:2009;EN 60950-1:2006 A1:2010;EN 60950-1:2006 A12:2011;EN 60950-1:2006 A2:2011*3;ETSI-EN 301489-34 V1.4.1;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053273685

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

2.35

PRODUCT NET WEIGHT

2.35

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053273685

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

130

PACKAGING WIDTH

215

PACKAGING LENGTH

345

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

9642750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

2.35

PACKAGING WEIGHT UNIT

KGM