Adjustable floor box kit raised floor 6 elements with 1 double socket, 1 dual UPS, 2 plates 2 RJ45 grey Simon 500 Cima

REF. **52006310-030**



BASIC INFORMATION

DESCRIPTION

Kit adjustable floor box, especially designed to be installed in raised floor of the signature Simon 500 Cimon and that is available for 6 elements with 1 double socket, 1 double UPS) and 2 RJ45. It is also compatible with flat snap-fit type RJ45 Keystone I, II, ATT ® / Avaya ®. Manufactured in plastic grey in colour and from the regulation UNE-EN 60.670-23, also have been used in its manufacture, metallic components with self-extinguishing thermoplastic insulation and halogen totally free of halogens, so that guarantees the no-propagation of the flame (in case of fire) and low toxicity (in the event of smoke generation). It measures 226 x 187 x 92 mm and for cleaning, just have to use a soft, dry cloth and do not cloths and / or cleaners that contain chlorine in their formulation, as they may damage the box.

FINISH

Grey

COMPATIBILITY

Simon 500 CIMA mechanisms

ETIM CLASS

EC000024

MATERIAL

Plastic

PACKAGING CONTENTS

Kit, metal partition wall, ground connection cable, screws and installation manual

REMARKS

To complete the installation of the product, as an option, it may be combined with flush-mount trim cover (ref.52053103-035) in cases where the same floor lining is not installed.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 1,5 to 2,5 mm

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the inclusion of protective foam

NUMBER OF CLAMP-HOLDER HOLES
8

NUMBER OF CONNECTIONS PER TERMINAL
1 terminal connection for click terminal connection system and 2 terminal connections for the fast terminal connection system

COMPATIBLE WITH CONNECTORS
Simon©, AMP netconnect© Standard 110, SL110, SL Tool-less, 216000 and 216005, Brand-Rex©, ADC Krone© KM8 Keystone, BeldenCDT© Giga Flex Keystone, Ersys©, General Cable©, Molex©, Panduit© Netkey, Ortronics© Clarity TechChoice Keystone, Rit© and other manufacturers with Keystone snap-fit system.

NUMBER OF CONNECTORS
4

RJ45 CONNECTORS
Not included

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+90 °C

DUST SHUTTER
Yes

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING
Secured by installing the metal partition wall in the housings fitted into the box for this purpose.

FORMAT
Schuko

HEAT RESISTANCE (°C)
+125°C (according rule IEC 60695-10-2)

IK CLASSIFICATION
08

INDICATOR FUNCTION
Yes

INSULATION RESISTANCE (V-MΩ)
>5 MOhms at 500V

CURRENT (A)
16 A

IP RATING
IP4X

LED CONSUMPTION INDICATOR (MA)
0.55

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)
1700kg

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60 °C

TYPE OF MECHANISM
Insertion

NUMBER OF MODULES
6 modules

NUMBER OF PLATES
2 voice and data plates

PLATE TYPE
Flat

RAL
7011

RECESS DIMENSION (MM)
170 x 210 mm

RJ45 ADAPTOR MODULE
Included in voice and data plates

NUMBER OF SIDE ENTRANCES
12

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

circuit and 1 double socket for stable current circuit

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
0

CLAW RANGE OF OPERATION (MM)
Between 14 and 54 mm

REMOVAL OF CONNECTOR

NUMBER OF COVER OPENING POSITIONS
2

EXTINGUISHING (ºC)
+850 ºC / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING
Using fastening claws on the raised floor tile (supplied with the floor box)

REMOVAL OF THE FRAME
Only with tool

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Specially designed to be installed in raised floors

REMOVAL OF THE PLATE
Only with tool

REMOVAL OF THE SOCKET
Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1
1 click connection (1 click®)

NUMBER OF TERMINALS
3 inputs and 3 outputs

REGULATIONS

REGULATIONS
UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053112632

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.58

PRODUCT NET WEIGHT
1.58

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053112632

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
0

PACKAGING WIDTH
0


PACKAGING LENGTH
0


PACKAGING VOLUME
0


PACKAGING GROSS WEIGHT
1.58


PACKAGING NET WEIGHT
1.58

PACKAGING WEIGHT UNIT
KGM


170
210


3
6
9


92<>120
54
14


227
220
simon
IP40