Voice and data flat plate with dust cover for 1 element and 2 RJ45 connectors category 6 UTP white Simon K45

REF. **KB96U/9**



BASIC INFORMATION

DESCRIPTION

Model of plate for Voice and data connections number KB96U / 9 belonging to the range of professionals Simon K45 elements and components, with capacity for compatibilizar with other series of Elements of the same range. It is a plate of voice and Data of character diffuser, with dust cover for 1 element, designed for 2 category 6 UTP RJ45 connectors with snap-fit Keystone I, II, ATT ® / Avaya ® Integrated insertion tool. Presents all the approvals Of security professionals, thanks to its metal components with insulation Self-extinguishing halogen-free thermoplastic that guarantees no flame propagation In case of fire and low toxicity in the event of Smoke. Measures 45x45mm and a Depth of 30 mm, you need element 90 ° positioner (ref. K66) to guide the plate into a vertical position in caos of Systems vertical enclosures.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 6 UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-26 AWG wiring

RJ45 CONNECTION
With insertion tool

CONNECTOR CHARACTERISTICS
Category 6 UTP

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (ºC)
+60º C

DUST PROTECTION
Yes

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (ºC)
-5 to 60º C

NUMBER OF MODULES
Half

PLATE TYPE
Flat

RAL
9003

RJ45 ADAPTOR MODULE
Supplied with voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0.3

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.035

PRODUCT NET WEIGHT

0.035

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436032071

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

88

PACKAGING WIDTH

123

PACKAGING LENGTH

136

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1472064

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.39

PACKAGING NET WEIGHT

0.35

PACKAGING WEIGHT UNIT

KGM