

Recessed movement and brightness detector 8m white IP54 3Y

REF. 89101112-130



BASIC INFORMATION

DESCRIPTION

PIR flush-mounted motion and light detector. The recommended installation height is 2.5 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 180°. The tangential detection range is 8 m and the radial detection range is 4 m.

The light regulation range is 2 - 2000 lux and the timing range is 8 s - 35 min. The configuration of the detector is done through potentiometers.

The control output is On/Off and the maximum switchable power is 1000 W (64 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 40 °C.

White finish, protection grade IP 54 and dimensions: Ø 78 x 89 mm.

3-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL

PUSH BUTTON

No

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

1000

RAL

9010

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION

HEIGHT

2.2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053369982

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING
MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME
UNIT

MMQ

UNITARY PACKAGING GROSS
WEIGHT

0.2

PRODUCT NET WEIGHT

0.116

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING EAN

8421053369982

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

130

PACKAGING WIDTH

90

PACKAGING LENGTH

90

PACKAGING MEASUREMENT
UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.2

PACKAGING NET WEIGHT

0.116

PACKAGING WEIGHT UNIT

KGM