

Optical sensor 10m 110° BT Mesh recessed box IP white IP20

REF. 89243523-130



BASIC INFORMATION

DESCRIPTION

Presence and brightness detector for flush mounting optical. The recommended installation height is 2.8 m, with a maximum height of 5 m. It has a detection angle of 110° and an opening angle of 110°. The tangential detection range is 10 m and the radial detection range is 10 m.

The brightness regulation range is . The detector configuration is done through a bluetooth and IP application.

Possibility of interconnection between sensors. The control protocol is IP.

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: 0 - 40 °C.

White finish, IP protection grade 20, and dimensions: Ø 125 x 75 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL

PUSH BUTTON

No

ETIM CLASS

EC001582

COMPATIBILITY

Simon Sensor Pro

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9016

POWER SUPPLY (V~)

Standard PoE (IEEE 802.3af)

CONTROL

IP

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.3

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053358184

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.418

PRODUCT NET WEIGHT

0.327

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053358184

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

130

PACKAGING WIDTH

90

PACKAGING LENGTH

135

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.418

PACKAGING NET WEIGHT

0.327

PACKAGING WEIGHT UNIT

KGM