

SUB-D25 connector (parallel port) female with trim plate aluminium Simon K45

REF. K104A/8



BASIC INFORMATION

DESCRIPTION

Simon, through its Simon K45 range, it provides all the elements and multimedia solutions required for its installation. In those cases which require a connection in parallel, this connector. Compatible with all direct snap-fit housings as well as the boxes in the Cima range, through the adaptor plates. Allows cabling according to its technical indications, and it is recommended in those places in which it is required a secure and convenient multimedia speed that is quick to place. Female SUB-D25 connector (parallel port) with trim plate. Aluminium finish, Simon K45 range. Terminal connection by welding. Installation by Insertion. Maximum recommended length of cabling: 30 meters, for more information, please refer to the product instruction sheet. Single plate of 2 elements and 4 modules, suitable for surface mounting and flush mounting. Supports from 0.2 to 0.5 mm Temperature it withstands: 5 to 40° C and -25 to 50° C. Metal components with self-extinguishing and halogen-free thermoplastic insulation that guarantees no flame propagation in case of fire and low toxicity in case of smoke dimensions 90x45 mm Clean with a soft, dry cloth, do not use abrasive cloths and / or abrasive cleaners containing chlorine.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Female SUB-D25 connector (parallel port)

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 30 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

NUMBER OF POSSIBLE ELEMENTS

2 elements

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

IP RATING

IP20

VERSION

Single

CONNECTOR TYPE

Sub-D25

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF WIRES

25

NUMBER OF CONTACTS

25

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45
and specific Simon 500 Cima
using adaptor (ref.50012088-
033)

INSTALLATION TYPE

Suitable for surface and flush
mounting

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
70

UNITARY PACKAGING WIDTH
93

UNITARY PACKAGING LENGTH
140

UNITARY PACKAGING
MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.038

PRODUCT NET WEIGHT
0.038

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8426436046221

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
911.4

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.19

PACKAGING NET WEIGHT
0.19

PACKAGING WEIGHT UNIT
KGM