

Modular Luminaire 720 Advance M4 120x30 NW 1-10V

REF. 72061140-884



BASIC INFORMATION

DESCRIPTION

Are you looking for a warm light quality? With a colour temperature of 4000° Kelvin this is the luminaire 720 modular Advance M4 120 x 30 NW 1-10V. The lighting of this series stands out for its high efficiency to perform a general lighting. With less light points lograremos better lighting that lights, this implies a energy savings of over 50%. Less lighting points with less power each, but with higher quality and brightness, its 34 Watts of power generated 4.100 lumens. It has a system of 1-10 V control, a white finish and an installation system for false ceiling with hardware. Like all the parts of this series, it stands out for its great durability and its Null maintenance. This is a LED technology of Simon that is able to generate more than 40,000 hours of constant light and without aberraciones chromatic, without the need for recámara the stand-alone or clean the luminaire.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

146 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

LUMENS (LM)

4100 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

4100 lm/28W

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Translucent

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

1-10 V

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

INSTALLATION TYPE

False ceiling, visible hardware

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053124857

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053124857

PACKAGING VOLUME

0.234

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

65

PACKAGING GROSS WEIGHT

5.56

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

300

PACKAGING NET WEIGHT

5

UNITARY PACKAGING GROSS
WEIGHT

5.56

PACKAGING LENGTH

1200

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

5