

Monobloc push button IP55 10AX 250V~ with quick terminal connection gray Simon Aqua

REF. 4400150-035



BASIC INFORMATION

FINISH

Grey

COMPATIBILITY

Simon 27 Mechanisms

ETIM CLASS

EC000029

TECHNICAL INFORMATION

IK CLASSIFICATION

07

IP RATING

IP55

MONOBLOCK

Yes

INDICATOR FUNCTION

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

7035

CURRENT (A)

10 AX

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018*1 | IEC 60884-1 Ed. 3.2*2 | UNE 20315-1-1:2017*2 | UNE 20315-1-2:2017*2 | EN IEC 60670-1:2021 + A11:2021*3 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.108

PACKAGING WIDTH

83

UNITARY PACKAGING WIDTH

0

PACKAGING LENGTH

222

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING
MEASUREMENT UNIT

MMT

PACKAGING EAN

8421053298411

PACKAGING VOLUME

1584636

UNITARY PACKAGING VOLUME

0

UNITS CONTAINED PACKAGING

5

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

86

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.54

MECANISMOS SIMON 27, 28 Y 44

Mecanismos básicos / Basic switches



Interruptor unipolar / Single-pole switch
XX00101-XX



Pulsador / Push button switch
XX00150-XX



Interruptor bipolar / Double pole switch
XX00133-XX



Conmutador / 2-way switch
XX00201-XX



Conmutador cruce / Intermediate switch
XX00251-XX

Mecanismos con piloto / Pilot switches



Interruptor unipolar / Single-pole switch
XX00102-XX



Interruptor bipolar / Double pole switch
XX00134-XX



Conmutador / 2-way switch
XX00202-XX



Interrupor unipolar / Single-pole switch
XX00104-XX



Pulsador / Push button switch
XX00160-XX



Conmutador / 2-way switch
XX2700204-XX



Conmutador cruce / Intermediate switch
XX2700254-XX