

Double schuko socket 16 A 250V~ with safety device, light indicator, and screw terminal white Simon Cima

REF. S1/9



BASIC INFORMATION

FINISH

White

COMPATIBILITY

With all the enclosures of the Simon Cima range.

ETIM CLASS

EC000125

TECHNICAL INFORMATION

FORMAT

Schuko

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

INDICATOR FUNCTION

Yes

CURRENT (A)

16 A

IP RATING

IP20

KIT AVAILABILITY

Yes

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MONOBLOCK

No

RAL

9003

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLATION DIRECTION

Horizontal, Vertical

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436016453

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0.3

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.112

PRODUCT NET WEIGHT

0.112

UNITARY PACKAGING WEIGHT UNIT

KGM

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

118

PACKAGING WIDTH

121

PACKAGING LENGTH

264

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3769392

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.12

PACKAGING NET WEIGHT

1.12

PACKAGING WEIGHT UNIT

KGM