

Back kit for 2 elements with 1 2P+E socket integrated with 2.1A USB charger with smartcharge and 2 two-way switches Simon 100

REF. 10010230-039



BASIC INFORMATION

FINISH

Black

PACKAGING CONTENTS

Mechanism and instructions

ETIM CLASS

EC002846

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

TYPE OF MECHANISM

Momentary switch / Insert button

VOLTAGE (V~)

230 V~

INSTALLATION AND MAINTENANCE

CLAW

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

universal

INSTALLATION DIRECTION

Horizontal

INSTALLATION TYPE

Suitable for flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

2-way Switch: 1 click connection (1 click®)

TYPE OF TERMINAL CONNECTION - FUNCTION 2

2P Socket / USB: Screw

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053225967

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053225967

PACKAGING VOLUME

1042800

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

75

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

88

PACKAGING NET WEIGHT

0.256

UNITARY PACKAGING GROSS
WEIGHT

0.256

PACKAGING LENGTH

158

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.256