

PD-20x3 Hallway HF+LUX recessed KNX white IP20

REF. 89215715-230



BASIC INFORMATION

DESCRIPTION

Presence and brightness detector for flush mounting HF. The recommended installation height is 2.8 m, with a maximum height of 3 m. It has a detection angle of 360° and an opening angle of 140°. The tangential detection range is 20 x 3 m and the radial detection range is 20 x 3 m.

The brightness regulation range is 10 - 1000 lux and the timing range is 0 s - 1092 min. The detector configuration is done via potentiometers and KNX.

It features TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The typical consumption is 30 mA.

The power supply voltage is KNX (21 - 30 VDC). The operating temperature of the detector is: -25 - 55 °C.

White finish, protection degree IP 20, and dimensions: 120 x 120 x 112 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

COMPATIBILITY

Simon Sensor Pro

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9010

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

CONTROL

KNX

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053357705

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.344

PRODUCT NET WEIGHT

0.206

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053357705

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

140

PACKAGING WIDTH

140

PACKAGING LENGTH

140

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.344

PACKAGING NET WEIGHT

0.206

PACKAGING WEIGHT UNIT

KGM