

Customisable on-desk set with 4 German socket outlets and 1 empty element aluminium Simon 400

REF. 42504000-133



BASIC INFORMATION

DESCRIPTION

For those who are looking for an electrical solution that can be set on the furniture, Simon has created this kit of desk top customizable with 4 socket outlets and one empty element finished in aluminium of the series Simon 400. All the products in this series have a protection fire-fighting thanks to its covers and fastenings that prevent the propagation of the fire and prevent the creation of fumes toxic as they are manufactured in self-extinguishing thermoplastic and halogen-free. Its great design and resistance are mirrored in its trim cover painted steel and its profile in anodised aluminium. It has 4 sockets for standard current circuit of 250 volts and 16 amps. Its dimensions are 250 x 120 x 80 millimetres and has a manual elevation system. The type of connector to the power is a Wieland® gst18i 3-pole male in-line with patch cord of 22 cm and to complete your installation, we must use the functions of Simon 400.

FINISH

Aluminium

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

NUMBER OF POSSIBLE ELEMENTS

1

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

NOMINAL VOLTAGE (V~)

250 V~

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9006

NUMBER OF REAR ENTRANCES

1

NUMBER OF SOCKETS

4 sockets for standard current circuit

VERSION

5 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

REMOVAL OF COMPONENTS

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure. Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

INSTALLATION TYPE

Suitable for fixing to furniture.

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053195871

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.05

PRODUCT NET WEIGHT

1.05

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053195871

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

285

PACKAGING WIDTH

125

PACKAGING LENGTH

95

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3384375

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.05

PACKAGING WEIGHT UNIT

KGM