

Flat voice and data plate with dust cover for 2 RJ45 Infra+® for 1 element white Simon 500 Cima

REF. 50015089-030



BASIC INFORMATION

DESCRIPTION

Composed of 1 element for 1 RJ45 BeldenCDT®, our flat base plate of voice and data flat plate with dust cover in aluminium finishes, the, it is part of the Simon 500 Cima series. It has measures of 50x50x11 mm and a thickness of 11 mmm. Its manufacture in halogen-free thermoplastic guarantees that there are no flame spread in case of fire is a notional case of fire and low toxicity very break loose any smoke. Finally, our plate includes clips for its set it in vertical and horizontal enclosures without the need of any adapter. In Simon we are aware that most concern to our customers. For this purpose, we have created our acclaimed Simon 500 Cima series, with which you will leave of worry to choose the best on the market in terms of security.

FINISH

White

PACKAGING CONTENTS

Flat voice and data plate with
dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

Yes

NUMBER OF MODULES

1

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

Infra+® RJ45 connectors.

IP RATING

IP20

RAL

9003

RJ45 CONNECTORS

Not included in voice and data plate

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Infra+® RJ45 connectors

SNAP-FIT TYPE

Infra+® RJ45 connectors

DUST PROTECTION

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053096864

PACKAGING VOLUME

0.604

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

54

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.186

PACKAGING WIDTH

52

PACKAGING NET WEIGHT

1.86

PRODUCT NET WEIGHT

0.186

PACKAGING LENGTH

215

PACKAGING WEIGHT UNIT

KGM

