

## Ledline 815 NW 600mm

REF. 81530033-984



## BASIC INFORMATION

### DESCRIPTION

This strip of LEDs part of the series LEDLINE 815 category A of the brand Simon and stands out for its quality. The LEDLINE 815 WW 600 provides neutral light and has a colour temperature of 3,900 K, with 750 lumens and 10 Watts. The control of this product is carried out by the system OJN / OFF and requires a power supply of 230 volts and a frequency of 50 / 60 Hertz rate. Its installation is very simple and is carried out directly on the surface-mounted where you want to place. It measures 600 x 33 millimetres and 22 millimetres of depth. Its beautiful finished in aluminium colour, which makes it perfect to be placed in any room of the home, office or premises. Moreover, its special features and structure you provide much versatility and a great functionality, since it can be used, but not only for lighting for decorating spaces. In this sense, the LEDLINE can be placed on objects or specific areas of the home or department for lighting and giving prominence, but another interesting option is used to highlight profiles. For example can be placed on both sides of a path of input at home, which will give it a very modern touch to the housing and illuminate at the same time, the path during the night. Thinking about its multiple possibilities, the LEDLINE 815 WW 600, it is designed to withstand both low and high temperatures ranging between - 15 and 40 degrees centigrade.

### APPLICATION

Ambient lighting,Alcove  
lighting,Furniture lighting

### PACKAGING CONTENTS

1 unit

### ETIM CLASS

EC000282

### REMARKS

Luminaires for interconnecting up to a maximum of 150W

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### DRIVER INCLUDED

Yes

### LUMENS (LM)

750 lm

### IP RATING

IP20

### ELECTRICAL CLASS

Type 1

### LUMENS/W

750 lm/10W

### OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

### INTEGRATED POWER SUPPLY

Yes

### OPTICS

General

### POWER SUPPLY (V~)

230 V~

### L70 (°C)

35,000 h at 25 °C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### COLOR TEMPERATURE (K)

3900 K

### LIGHT BEAM APERTURE ANGLE (°)

120°

### POWER (W)

10 W

### CONTROL

On/Off

### COLOR TYPE

NW

### SERVICE LIFE

30.000 h

### CRI

80

### LIGHTING EFFICIENCY (LM/W)

75 lm/W

### CHROMATICS CRI ICONS

CRI  
80

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Surface

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

## REGULATIONS

### WARRANTY

3 years 30,000 h

## LOGISTICS INFORMATION

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.228

### PRODUCT NET WEIGHT

0.228

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053122587

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

25

### PACKAGING WIDTH

35

### PACKAGING LENGTH

670

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

0.586

### PACKAGING VOLUME UNIT

DMQ

### PACKAGING GROSS WEIGHT

0.228

### PACKAGING NET WEIGHT

0.228

### PACKAGING WEIGHT UNIT

KGM