


**Flat voice and data plate without dust cover 1 element for
1 RJ45 compatible other manufacturers aluminium Simon
500 Cima**

REF. 50000185-033



BASIC INFORMATION

DESCRIPTION

Designed for one element and one or two RJ45 connectors, this plate of voice and data flat plate, it is part of the Simon 500 Cima series. The piece has no dust shutter and it is suitable to be used with components from other manufacturers. Its design finished in aluminium provides versatility and sophistication in environments chosen for the installation. These plates are ideal to be used in working environments, you need to connect several elements of voice and data. This is the individual version of a module if you want to incorporate the plate Simon 500 Cima, aluminium, to any enclosure vertically or horizontally, the clips for this are included in the kit. The dimensions of the product are of 50 x 50 mm and 11 mm of depth. The manufacturing materials provide quality and security, thanks to the components isolated with halogen-free thermoplastic, which does not propagate the fires. Easy maintenance, it is not recommended to use abrasive cleaners that contain chlorine.

FINISH

Aluminium

PACKAGING CONTENTS

Flat voice and data plate without
dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

Plate for 1 and 2 RJ45

COMPATIBLE WITH CONNECTORS

Simon®, ADC Krone® KM8 Keystone Series, AMP netconnect® Serie Standard 110, SL110, SL Tool less, 216000 and 216005, BeldenCDT® GigaFlex Keystone Series, Brand-Rex®, Ersys®, General Cable®, Molex®, Panduit® Netkey Series, Ortronics® Clarity TechChoice Keystone Series, Rit®, Systimax® and manufacturers of RJ45 with Keystone I and II format snap fitting.

RJ45 CONNECTORS

Not included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

DUST PROTECTION

No

DUST SHUTTER

No

FORMAT

RJ45

IP RATING

IP20

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

1

PLATE TYPE

Flat

RJ45 ADAPTOR MODULE

Included in voice and data plate

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053095294

PACKAGING VOLUME

1.472

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

88

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.027

PACKAGING WIDTH

123

PACKAGING NET WEIGHT

0.54

PRODUCT NET WEIGHT

0.027

PACKAGING LENGTH

136

PACKAGING WEIGHT UNIT

KGM

