Customisable kit with cover and brush, 1 schuko socket outlet and 3 empty elements white S400 Indesk

REF. **44401000-130**



BASIC INFORMATION

DESCRIPTION

Kit within the table customizable, belonging to the series Simon 400 Indesk and which has cover, brush strip, 1 socket for Schuko plugs and 3 empty elements. It has dimensions of 250 x 185 x 85 mm, it is manual elevation and access to the cabling is done with brush strip. Its current is 16 A and works with a voltage of 250V. The installation is carried out by flush mounted in furniture and using the claws that incorporate or with screws through the holes available and to complete the installation of the product, it must be combined with the Simon 400 Indesk (references 4000XXX-03X). The installation, it is always you must perform in places with a temperature between -5 to 60 ° C, although it can withstand extreme temperatures. In the manufacture of this kit customizable required for the anodised aluminium profile, painted steel for the enclosure thermoplastic and halogen-free, self-extinguishing for the fastenings and covers. To clean this kit, just use a soft, dry cloth.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with brush

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

NUMBER OF POSSIBLE ELEMENTS
3

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

NOMINAL VOLTAGE (V~)
250 V~

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9016

NUMBER OF REAR ENTRANCES
3

RECESS DIMENSION (MM)
228 x 175 mm (± 2mm)

NUMBER OF SOCKETS
1 socket for standard current circuit

VERSION
4 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS
With brush

CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

REMOVAL OF COMPONENTS

NUMBER OF COVER OPENING POSITIONS
1

EXTINGUISHING (ºC)
+70 ºC (according to standard IEC 60670)

TYPE OF FASTENING
By lateral tightening of claws provided with the enclosure. Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

REMOVAL OF THE FRAME
Only with tool

INSTALLATION TYPE
Suitable for recessed mount in furniture.

OPENING ORIENTATION
At 45

REMOVAL OF THE PLATE
Only with tool

SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS
Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053196212

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.7

PRODUCT NET WEIGHT
1.7

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053196212

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
275

PACKAGING WIDTH
192

PACKAGING LENGTH
95

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
5016000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.7

PACKAGING WEIGHT UNIT
KGM