

Schuko socket base monobloc 10-16A 250V~ with lateral earthing with screw terminal connection for surface mounting gray Simon Aqua

REF. 4490472-035



BASIC INFORMATION

FINISH

Grey

COMPATIBILITY

Simon 27 mechanisms

ETIM CLASS

EC000125

TECHNICAL INFORMATION

FORMAT

Schuko

CURRENT (A)

16 A

MONOBLOCK

Yes

IK CLASSIFICATION

07

IP RATING

IP55

RAL

7035

INDICATOR FUNCTION

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

15

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018*1 | IEC 60884-1 Ed. 3.2*2 | UNE 20315-1-1:2017*2 | UNE 20315-1-2:2017*2 | EN IEC 60670-1:2021 + A11:2021*3 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.048

PACKAGING LENGTH

306

UNITARY PACKAGING WIDTH

0

PRODUCT NET WEIGHT

0.048

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

4078980

UNITARY PACKAGING
MEASUREMENT UNIT

MMT

PACKAGING EAN

8421053298794

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

86

PACKAGING NET WEIGHT

0.48

PACKAGING WIDTH

155

PACKAGING WEIGHT UNIT

KGM