German socket outlet 16A 250V~ with safety device and fast terminal connection champagne Simon 31

REF. **31464-64**

BASIC INFORMATION

DESCRIPTION

Schuko socket outlet with safety device (as the covers include the child protection function) and quick terminal connection, in champagne colour and belonging to the series Simon 31. This socket-outlet has a current of 16 A and a voltage of 250V, in addition to a operation is by insertion. It has 2 modules and supports a section of wire 2.5 mm with a stripped 13 mm Complies with the European standards and regulations UNE 20315-1-1: 2009, UNE 20315-1-2: 2009 and can be installed on surfaces with a temperature located between 5 and 40ºC, approximately, although it ' s true that can withstand extreme temperatures of -25 to 50ºC, plus or minus. Its dimensions are 64x65 mm and it is manufactured with metal components with halogen-free insulation and trim metallized thermoplastic. For a correct maintenance to this realizarle socket-outlet, it will only need to wipe it with a soft and dry cloth, without having to use abrasive cloths or cleaners that contain chlorine in its formula.

FINISH

Champagne

COMPATIBILITY

Simon 31 frames

PACKAGING CONTENTS

Socket outlet with cover

REMARKS

The covers include a child-proof protective feature.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
2,5 mm

NUMBER OF POSSIBLE ELEMENTS
1 element

FORMAT
Schuko

INDICATOR FUNCTION
No

CURRENT (A)
16 A

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM
Insertion

MONOBLOCK
No

NOMINAL VOLTAGE (V~)
250 V~

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
13

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

REGULATIONS

REGULATIONS
UNE 20315-1-1:2009, UNE 20315-1-2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
3026595

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.1

PRODUCT NET WEIGHT
0.1

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053055670

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
83

PACKAGING WIDTH
165

PACKAGING LENGTH
221

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3026595

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.995

PACKAGING NET WEIGHT
1

PACKAGING WEIGHT UNIT
KGM