

3RCA connector female with trim plate black Simon K45

REF. K105B/14



BASIC INFORMATION

DESCRIPTION

This connector is within the range of products Simon K45 and it is a 3RCA connector, female, which has included the trim plate. Its innovative black colour endow elegance to the place of the room where it is placed, its installation is very simple and is carried out by means of flush mounted or directly on the surface-mounted, allowing both options to the consumer tastes. It measures 22.5 millimetres by 45 millimetres. Its type of clamping is screwed and its operation is by insertion. The maximum wire length recommended for the connector is 20 meters. The product is manufactured with metal components with halogen-free thermoplastic insulation. This provides to the connector a character self-extinguishing, or the same thing, it provides the ability to propagate the spread in case of fire and reduces the toxicity of smoke, which translates into a high security.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Female 3RCA connector, cable fixing clamp and instruction sheet

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 20 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

FORMAT

RCA

RAL

7021

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

CONNECTOR TYPE

RCA

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

NUMBER OF CONTACTS

9

NUMBER OF WIRES

9

NUMBER OF POSSIBLE ELEMENTS

1/2 element

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436064737

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8426436064737

PACKAGING VOLUME

0.105

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

50

PACKAGING GROSS WEIGHT

0.023

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

42

PACKAGING NET WEIGHT

0.023

UNITARY PACKAGING GROSS
WEIGHT

0.023

PACKAGING LENGTH

50

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.023