

Adjustable depth cover for 2 modules S for installation in false floor gray Simon CIMA

REF. SF210/1



BASIC INFORMATION

FINISH

Grey

MATERIAL

Various

COMPATIBILITY

With Simon Cima mechanisms
and Simon 27 Play/Simon K45
(via adapter)

ETIM CLASS

EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES

4

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

1400kg

RAL

7011

RECESS DIMENSION (MM)

170 x 155 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

REMOVAL OF THE FRAME

Only with tool

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436052550

PRODUCT NET WEIGHT

1.055

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

3.325

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436052550

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.15

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

100

PACKAGING NET WEIGHT

1.055

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

190

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

1.055

PACKAGING LENGTH

175