

Downlight 725.25 NW Comfort High Flux

REF. 72525030-884



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

IP RATING

IP44

DRIVER INCLUDED

Yes

LUMENS (LM)

3400 lm

OPERATING TEMPERATURE RANGE (°C)

-10 - 35 °C

L70 (°C)

30,000 h

LUMENS/W

3400 lm/37W

COLOR TEMPERATURE (K)

4000 K

LIGHT BEAM APERTURE ANGLE (°)

120°

OPTICS

General

CONTROL

On/Off

COLOR TYPE

NW

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CRI

80

LIGHTING EFFICIENCY (LM/W)

91,9 lm/W

POWER (W)

37 W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface-mounted

INSTALLATION TYPE

Flush-mounted

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053089668

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.018

PRODUCT NET WEIGHT

0.796

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053089668

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

117

PACKAGING WIDTH

257

PACKAGING LENGTH

257

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

7727733

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.018

PACKAGING NET WEIGHT

0.796

PACKAGING WEIGHT UNIT

KGM