

## Customisable kit with cover and fin, 4 schuko socket outlets and 2 empty elements white S400 Indesk

REF. 45604000-130



## BASIC INFORMATION

### DESCRIPTION

Count on several devices in a single element, is a great advantage for electrical installations. This condition is possible with the kit is part of the table customizable with cover and fin, 4 Schuko socket outlets and 2 empty elements in white colour of the series Simon 400 Indesk. With a current of 16 A and a voltage of 250 V ~, this is a product suitable to be flush mounted in furniture, which is compatible with the rest of the functions of this range. It is composed of enclosure painted steel, profile in anodised aluminium, covers and fastenings in self-extinguishing thermoplastic and halogen-free that prevent fire and gases in case of fire. 340 x 185 x 85 mm are its dimensions. It also has a connector figure Wieland ® gst18i with 3 poles male in-line with patch cord of 22 cm, insulation resistance > 5 M? at 500 V and dielectric strength with no holes or contours with 2000 V at 50H during a minute.

### FINISH

White

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

### ETIM CLASS

EC002759

### REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### FORMAT

Schuko

### NOMINAL VOLTAGE (V~)

250 V~

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with metal fin

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

### RAL

9016

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### IP RATING

IP30

### NUMBER OF REAR ENTRANCES

2

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### RECESS DIMENSION (MM)

318 x 175 mm (± 2mm)

### NUMBER OF POSSIBLE ELEMENTS

2

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

### NUMBER OF SOCKETS

4 sockets for standard current circuit

### VERSION

6 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS

With metal fin

### CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

### REMOVAL OF COMPONENTS

### NUMBER OF COVER OPENING POSITIONS

1

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure.

Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION TYPE

Suitable for recessed mount in furniture.

### OPENING ORIENTATION

At 45°

### REMOVAL OF THE PLATE

Only with tool

### SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053085592

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

2.35

### PRODUCT NET WEIGHT

2.35

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053085592

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

365

### PACKAGING WIDTH

195

### PACKAGING LENGTH

90

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

6405750

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

2.35

### PACKAGING WEIGHT UNIT

KGM