

Watertight luminaire 789 48W 4000K 1500

REF. 78938033-884



BASIC INFORMATION

DESCRIPTION

Waterproof lighting fixture for applications such as parking lots, garages, and technical areas, designed to provide uniform and comfortable lighting in circulation areas. Linear design with high uniformity opal diffuser for homogeneous light distribution, minimizing shadows and glare. Through wiring and double connector included, allowing a continuous run of up to 10 light fixtures per line. Installation type: Surface. Optics: 120. Color temperature: 4000K. Power: 48W. Lumens: 4800lm. Efficiency: 100lm/w. Protection rating IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 1565 mm x 65 mm x 65 mm.

APPLICATION

Parking, Industrial
lighting, General lighting, Car
park lighting

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

08

IP RATING

IP65

OPERATING TEMPERATURE RANGE (°C)

-25...+40

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

100 lm/W

LUMENS (LM)

4800 lm

OPTICS

General

POWER (W)

48 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053440254

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.04

PRODUCT NET WEIGHT

0.96

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053440254

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

225

PACKAGING WIDTH

300

PACKAGING LENGTH

1620

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

109350000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

12.48

PACKAGING NET WEIGHT

0.96

PACKAGING WEIGHT UNIT

KGM