Front trim cover 3 metres for columns aluminium Simon K45

REF. **RALK013/8**



BASIC INFORMATION

DESCRIPTION

The trim front cover of the Simon K45 range is ideal for columns of three metres of the same range in aluminium finish. This is the perfect to integrate a column of these features in the ambience of the room or department where it is installed, making the most of the element in a place without break with the decorative line. This front cover is easy to install and maintenance, and also has multiple possibilities since it is compatible with several products: Columns of one side of the two sides, square, columns and columns of four faces. Its manufacturing with anodised steel makes it highly resistant to possible knocks and scratches. To do this, the usual steel we electrochemical to a process which results in this material of great durability, which duplicates the hardness and robustness of stainless steel and that extends considerably the service life of the product.

FINISH

Metal

PACKAGING CONTENTS

Front trim cover

MATERIAL

Aluminium

ETIM CLASS

EC000461

REMARKS

Product envisaged as a replacement part, in the event of loss or substitution. It is compatible with the 1-sided, 2-sided square and 4-sided columns. Supplied extruded in anodised aluminium.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

1-sided, 2-sided (square and oval) and 4-sided

DIELECTRIC STRENGTH

Without perforation or contournament with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

EARTHING RESISTANCE

< 0.05 ?

HEAT RESISTANCE (°C)

+650°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 120° C

VERSION

1-sided, 2-sided (Square) and 4-sided

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER
Only with tool

TYPE OF FASTENING
Through direct snap-fit on the column (does not require the use of tools for fastening)

INSTALLATION DIRECTION
Vertical

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436056442

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.225

PRODUCT NET WEIGHT
1.225

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436056442

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
60

PACKAGING WIDTH
60

PACKAGING LENGTH
3020

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
10.872

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.225

PACKAGING WEIGHT UNIT
KGM