

Spotlight 640.10 Flush mount Amber Wide Flood White

REF. 64010030-482



BASIC INFORMATION

DESCRIPTION

Model spotlight for Lighting in indoor reference number 64010030-482, designed especially for flush mount surfaces making a professional assembly With stable and focused light. It is a model of The 640 spotlight range with rail with great performance, type of lighting colour Amber and values of optics WIDE FLOOD, assembly to socket with a larger of rail Line of the orientation of the light. It has an ON-OFF electric control, with values of power up to 23 W, model designed for flush mounting, colour, tone and finishes in white, with dimensions of 100x102 Mm, ideal for small spaces and corners

APPLICATION

Accent lighting, General lighting

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DIRECTIONAL

Yes

LUMENS (LM)

2600 lm

IP RATING

IP20

DRIVER INCLUDED

Yes

LUMENS/W

2600 lm/30W

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

ELECTRICAL CLASS

Type 1

OPTICS

Wide Flood

POWER SUPPLY (V~)

120/240 V~

L70 (°C)

100,000 h at 25° C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

2500 K

L90 (°C)

30,000 h at 25 °C

POWER (W)

30 W

CONTROL

On/Off

COLOR TYPE

Amber

SERVICE LIFE

50.000 h

LIGHTING EFFICIENCY (LM/W)

87 lm/W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Flush mount

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.4

PRODUCT NET WEIGHT

1.184

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053138007

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

200

PACKAGING LENGTH

250

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

8000000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.4

PACKAGING NET WEIGHT

1.184

PACKAGING WEIGHT UNIT

KGM