

Module for 1 Keystone I RJ45 AMP®, Krone® or BeldenCDT® in angled voice and data plates

REF. MD64



BASIC INFORMATION

DESCRIPTION

This module is ideal for 1 Keystone I RJ45 from AMP®, Krone® or BeldenCDT® in angled voice and data of the Simon 500 Cima series. It is necessary to point out that this product is only for voice and data plates of type plates, as the angled voice and data plates for Simon as are included the module required. The module is very simple installation and has a surface-mounted 32 x 20 millimetres and 10 millimetres of depth. The materials that Simon used to manufacture its products are of high quality. This enables you not only a good operation floor of the products, but this occurs during a long period of time. Therefore, Simon is committed to the strength and by components that 's this features to the products. This is the case of the halogen-free thermoplastic with which it is manufactured this module. This material is not only capacita to the module to operate in intervals of temperatures ranging from -5 and 60 degrees centigrade. Also, another advantage that comes this material is that contribute to flame spread in case of fire and reduce the capability of smoke, which gives much security to the final set.

COMPATIBILITY

Simon 500 Cima and Simon K45 angled voice and data plates

PACKAGING CONTENTS

MD Module for 1 RJ45

ETIM CLASS

EC002948

REMARKS

The MD Module can only be combined with angled voice and data plates (flat voice and data plates include the MD Module on the plate itself).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

MD Module for 1 RJ45

COMPATIBLE WITH CONNECTORS

ADC Krone® Serie KM8 Keystone, HK Keystone, AMP netconnect® 216000 and 216005, BeldenCDT® Serie Giga Flex Keystone, Ersys®, Molex®, Ortronics® Serie Clarity TechChoice Keystone and Siemon® Serie MAX Keystone

RJ45 CONNECTORS

Not included in the MD Module

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

FORMAT

RJ45

KIT AVAILABILITY

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

SNAP-FIT RJ45 PLATES

RJ45 AMP®, Krone® or BeldenCDT® connectors

SNAP-FIT TYPE

RJ45 AMP®, Krone® or BeldenCDT® connectors

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION

Vertical, corresponding with the MD Module fastening slots

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.002

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

455000

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436025387

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

50

PACKAGING GROSS WEIGHT

0.1

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

65

PACKAGING NET WEIGHT

0.1

UNITARY PACKAGING GROSS

WEIGHT

0.002

PACKAGING WIDTH

70

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

100