

Rocker with viewer for switch with pilot light for 1 element white Simon K45

REF. K115/9



BASIC INFORMATION

DESCRIPTION

With the versatility of in white finishes that combine with all kinds of environments, the rocker with viewer for 2-way switch of the collection Simon 45, achieved innovation, the perfect balance between functionality and design. The rocker with viewer in this range, includes pilot light to indicate whether the load on which acts is on or off. However, it is not possible to combine 2 narrow rocker for control mechanisms with in a adaptor plate Simon 500 Cima-Simon 45. It is made up of halogen-free thermoplastic, to protect the room of the flame spread and toxicity by smoke in case of fire. It can reach temperatures of more than 60 ° C, with recommended installation from -5 to 60 °C. It has a size of 45 x 22.5 mm and a depth of 10 mm, and is designed for an installation both recessed and surface-mounted and includes signaling function for beacon the mechanism and place it into moments of a low lighting.

FINISH

White

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Rocker and installation manual

ETIM CLASS

EC000011

REMARKS

It is not possible to combine 2 narrow button control mechanisms on a Simon 500 Cima-Simon K45 adapter plate

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

AVAILABLE IN

Quarter and half module versions

KIT AVAILABILITY

No

NUMBER OF MODULES

Four

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

9003

INDICATOR FUNCTION

Yes

VERSION

Single

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436047198

PRODUCT NET WEIGHT

0.006

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

544320

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436047198

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.62

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

72

PACKAGING NET WEIGHT

0.06

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

72

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.006

PACKAGING LENGTH

105