

German socket outlet 16A 250V~ with safety device and fast terminal connection ivory Simon 27 Play

REF. 27432-62



BASIC INFORMATION

DESCRIPTION

Shuko socket-outlet with an intensity of 16 A and a power of 250 V~ also includes a safety device, fast terminal connection, its finish is ivory in colour and you can find it in the category "outlets" of the Simon 27 Play series, the lids include the child protection function. Its installation, it is suitable to be recessed or surface-mounted, so you will have both ways choosing the one that best suits your home. The elements of the Simon 27 Play range are to enjoy decorating, this way you have created a concept to decorate the different spaces of your home, take advantage of the great variety when it comes to customizing the elements that the collection offers, you will have frames for intermediate piece, hinged cover and rocker sleeve in different finishes to adapt the element in any corner of the home.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Socket outlet with cover

ETIM CLASS

EC000125

REMARKS

The covers include a child-proof protective feature.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	CURRENT (A) 16 A	MONOBLOCK No
CABLE SECTION ADMITTED (MM) 2,5 mm	IP RATING IP20	OPERATING TEMPERATURE RANGE (°C) 5 - 40 °C
NUMBER OF POSSIBLE ELEMENTS 1 element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
FORMAT Schuko	TYPE OF MECHANISM Insertion	VERSION Single
INDICATOR FUNCTION No		VOLTAGE (V~) 250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 15	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal, American and Centralisations	INSTALLATION TYPE Suitable for surface and flush mounting
CLAW Simon 27	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Fast

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | UNE 20315-1-1:2017 | IEC 60884-1 Ed 3.2 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053252086

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.055

PRODUCT NET WEIGHT

0.055

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053051498

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

53

PACKAGING WIDTH

105

PACKAGING LENGTH

221

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1229865

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.515

PACKAGING NET WEIGHT

0.55

PACKAGING WEIGHT UNIT

KGM