

Kit Flash 90 consisting of schuko modular power socket, USB Type C Dock including 1x HDMI + LAN + 3x USB Type A, USB charger Type C 20W and grommet (cable outlet) black Simon K45

REF. KR3311301/14



BASIC INFORMATION

DESCRIPTION

Kit Flash 90 based on a modular schuko power socket-outlet for installation in furniture with an optional protective lid to allow it to be closed and hide the connections when not in use. Includes a USB Type-C dock with 1 HDMI output for display, 1 Gigabit Ethernet port, and 3 USB Type-A connectors for keyboard, mouse, and any other connection device based on the USB Type-A connector. The kit includes a 20W USB Type-C charger and a cable outlet in a black finish. Supplied with a 20cm long patch cable terminated in a 3-pole Wieland® Gst18i male aerial quick connector with a safety anchor to facilitate safe connection and disconnection from the mains without interrupting the power supply. The kit is supplied assembled with the internal connections pre-made. It is only necessary to make the die in the furniture where the product will be fixed and once done, connect it to the mains for it to be functional. It requires ordering the dock power supply separately (ref. CR6100121150201/14)

FINISH

Black

MATERIAL

Plastic

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 A

SNAP-FIT RJ45 PLATES

Directly to the Dock

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

Yes

IP RATING

IP20

SNAP-FIT TYPE

Embedded in the dock

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Protective lid available (as an option) to protect the connections against entry of dust and small objects

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

USB CHARACTERISTICS

Charging

RJ45 CONNECTORS

Yes

NOMINAL VOLTAGE (V~)

250 V~

USB CURRENT (A)

2,2 A

CONNECTOR TYPE

Schuko

RAL

9005

POWER DELIVERY USB

Yes

NUMBER OF CONTACTS

3

RECESS DIMENSION (MM)

ø80 mm

QUICK CHARGE USB

Yes

FORMAT

Schuko

RJ45 ADAPTOR MODULE

Yes

USB VOLTAGE (V~)

9 V~

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

No tools needed

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REMOVAL OF COVER

Only with tool

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD*1 | Dir. 2014/30/UE EMC*3 | Dir. 2011/65/UE RoHS + post. mod.*1 | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) *1 *13 *12 | S.I. 2016 No. 1101 - The Electrical Equipment (Safety) Regulations 2016*2 | S.I. 2012 No. 3032 - The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012*2 | IEC 60884-1 Ed.3.2*1 | BS 1363-2:2016+A1:2018*2 | UNE 20315-1-1:2017*5 | BS 1363-4:2016+A1:2018*2 | UNE 20315-1-2:2017*5 | DS 60884-2-D1:2023*4 | CEI 23-50 V4*7 | SANS 164-1:2021*6 | SN 441011-2-1:2019*9 | SI 32 Fig. 204 B*8 | AS/NZS 3112:2017*11 | EN 50173-1:2018*10 | EN 50563:2011 + A1:2013*13 *12 | EN 55032:2015 + A11:2020 + A1:2020*12*14 *16 | EN 62368-1: 2014 + A11:2017*13 *12 | EN 55035:2017 + A11:2020*12*14 *16 | ETSI-EN 301489-34 V2.1.1*13 | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024*12 *16 | EN IEC 60670-1:2021+ A11:2021*15 | EN 61000-3-3:2013 +A1:2019 + A2:2021 *12 *16 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053398128

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.211

PRODUCT NET WEIGHT

0.192

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053398128

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

120

PACKAGING WIDTH

130

PACKAGING LENGTH

252

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3931200

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.793

PACKAGING NET WEIGHT

0.192

PACKAGING WEIGHT UNIT

KGM