

Wall movement and brightness detector 140° 14m white IP54

REF. 89102142-430



BASIC INFORMATION

DESCRIPTION

PIR wall motion and brightness detector. The recommended installation height is 2 m, with a maximum height of 4 m. It has a detection angle of 140°. The tangential detection range is 14 m and the radial detection range is 3 m.

The brightness regulation range is 2 - 2000 lux and the timing range is 8 s - 35 min. The detector configuration is done through potentiometers.

The control output is On/Off and the maximum switchable power is 2000 W (250 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C.

White finish, IP 54 protection rating, and dimensions: 86 x 82 x 99 mm.

5 years warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9010

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

1.8

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053341544

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.246

PRODUCT NET WEIGHT

0.172

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053341544

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

153

PACKAGING WIDTH

90

PACKAGING LENGTH

76

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1046520

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.246

PACKAGING NET WEIGHT

0.172

PACKAGING WEIGHT UNIT

KGM