

IP66 watertight raised floor box kit with 2 schuko socket outlets + 1 narrow blind cover and sheath

REF. KGH210RF/74



BASIC INFORMATION

DESCRIPTION

Simon completely renovates its range of watertight floor boxes for indoor and outdoor environments. This is a kit that includes the manual closure mechanism frame with 2 schuko sockets and 1 K45 blind plate of 22.5x45mm, designed to integrate into the included base for installation in raised flooring with cutting dimensions of 174 x 125 mm. The product design, combined with its stainless steel mechanism frame, ensures a robust, solid, and safe installation as it can withstand a water jet of 1 kg/cm² from any direction, achieving an IP66 protection rating when the cover is closed. It also supports a maximum load of 1500 kg and has an IK08 impact resistance. It maintains an optimal bending radius of wiring in high-category voice and data connections. Our accessory for plug connection with the cover closed is available, so we can keep our connections active with an IP54 (see reference KFA1001), the possibility to level our box in case of irregular flooring (see reference KFA1003), or the ability to chain multiple boxes together (see reference KFA1002).

FINISH

Black

COMPATIBILITY

K45 Solutions

MATERIAL

Polycarbonate

ETIM CLASS

EC000024

TECHNICAL INFORMATION

FORMAT

Schuko

IP RATING

IP66

MAXIMUM LOAD (KG)

2000 Kg - Closed box | 250 Kg - Open box

IK CLASSIFICATION

08

KIT AVAILABILITY

Yes

RECESS DIMENSION (MM)

125x174

CURRENT (A)

16 A

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

REMOVAL OF THE SOCKET

Only with tool

NUMBER OF COVER OPENING POSITIONS

1

REMOVAL OF THE FRAME

Only with tool

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60670-23:2008 | EN IEC 63000:2018 | IEC 60884-1 Ed 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053355664

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

1.319

PRODUCT NET WEIGHT

1.214

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053355664

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

1020

PACKAGING WIDTH

1580

PACKAGING LENGTH

2170

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3497172000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.319

PACKAGING NET WEIGHT

1.214

PACKAGING WEIGHT UNIT

KGM