

Custom button box 2 wait/enter functions for homes and offices graphite Simon 82 Sense

REF. 8000623-038



BASIC INFORMATION

FINISH

Graphite

PACKAGING CONTENTS

Keypad and instructions

MATERIAL

Thermoplastic

ETIM CLASS

EC000205

REMARKS

Requires installation on LON or KNX bus coupling unit (8000100-039 or 8400100-039). Possibility of customising and creating your own configuration by choosing the functions you need from our icon library.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

NUMBER OF POSSIBLE ELEMENTS

1 element

INDICATOR FUNCTION

Yes

CURRENT (A)

6,2 mA

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Touch

OPERATING TEMPERATURE RANGE (°C)

0 - 45 °C

POWER SUPPLY (V~)

24 Vdc

RELATIVE HUMIDITY

From 20 to 85% (without condensation)

SLIDE CONTROL

No

SOUND FEEDBACK

Yes

STORAGE TEMPERATURE RANGE (°C)

25 - 70 °C

VIBRATION FEEDBACK

Yes

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-5:2016

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053128497

UNITARY PACKAGING HEIGHT

77

UNITARY PACKAGING WIDTH

137

UNITARY PACKAGING LENGTH

137

UNITARY PACKAGING
MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

1445213

UNITARY PACKAGING VOLUME
UNIT

MMQ

UNITARY PACKAGING GROSS
WEIGHT

0.033

PRODUCT NET WEIGHT

0.033

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING EAN

8421053128497

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

77

PACKAGING WIDTH

137

PACKAGING LENGTH

137

PACKAGING MEASUREMENT
UNIT

MMT

PACKAGING VOLUME

129.688

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.033

PACKAGING WEIGHT UNIT

KGM