

**Complete kit with cover, brush, 2 schuko socket outlets, 2
UPS socket outlets and plate for 2 RJ45 connectors white
S400 Indesk**

REF. 44502220-130



BASIC INFORMATION

DESCRIPTION

A piece created to flush mount inside the table and allow easy access to it thanks to its manual lifting system. We are looking at a complete kit with cover and brush, for 2 schuko sockets, 2 UPS sockets, and a plate for 2 RJ45 connectors, made of metal with a white finish and belonging to the Simon 400 Indesk series. For a voltage of 250 volts and an intensity of 16 amperes, it has a Wieland® gst18i connector with three male aerial poles with a 22 cm patch cord, and its dimensions are 295 x 185 x 85 millimeters. This piece stands out for its impact resistance due to its painted steel enclosure and anodized aluminum profile. Another fundamental characteristic is its fire resistance, thanks to its covers and supports made of self-extinguishing thermoplastic and halogen-free, which will prevent flame spread and the creation of toxic fumes.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INSULATION RESISTANCE (V-MΩ)

>5 M? at 500 V

RAL

9016

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

CURRENT (A)

16 A

RECESS DIMENSION (MM)

273 x 175 mm (± 2mm)

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

IP RATING

IP30

NUMBER OF RJ45 WINDOWS

2

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone❖ I, II and Systimax❖

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60❖C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60❖ C

SNAP-FIT TYPE

Keystone❖ I, II and Systimax❖

FORMAT

Schuko

OPERATING TEMPERATURE RANGE (°C)

-5...+60

NUMBER OF SOCKETS

2 sockets for standard current circuit and 2 sockets for stable current circuit (UPS)

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

TYPE OF POWER SUPPLY CONNECTOR

Wieland❖ GST 18i male 3-pole overhead connector with 22 cm patch cord

NUMBER OF UPS SOCKET OUTLETS

2

IK CLASSIFICATION

07

VERSION

5 elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With brush

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45°

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053208182

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

2.215

PRODUCT NET WEIGHT

2.215

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053208182

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

275

PACKAGING WIDTH

195

PACKAGING LENGTH

90

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4826250

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

2.215

PACKAGING WEIGHT UNIT

KGM