Simon SM34 Wall Charging Point with 5m Cable T2 Single-Phase 7.4 kW + Bluetooth + Automatic and Differential + Surge Protection with Automatic Meter Reset

REF. **0651042-400**



BASIC INFORMATION

FINISH
Graphite

APPLICATION
Residential

ETIM CLASS
EC002883

MATERIAL
ABS Plastic

OPERATING ENVIRONMENT
Residential

TECHNICAL INFORMATION

CONNECTOR TYPE
Type 2 Straight cable

CURRENT (A)
32 A

MODE 3 STATUS INDICATOR
Yes

FREQUENCY
50 Hz

IP RATING
IP54

NUMBER OF OUTLETS
1

IK CLASSIFICATION
10

TYPE OF LINE
Single-phase

REGULATIONS

REGULATIONS
Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | Dir. 2014/53/UE RED*1 | EN IEC 61851-1:2019 | EN IEC 61851-21-2:2021 | EN 62196-2:2017 | EN 62311:2008 | EN IEC 63000:2018 | ETSI EN 300 328 v2.2.2*1

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053301340

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
5.665

PRODUCT NET WEIGHT
5.665

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053301340

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
149

PACKAGING WIDTH
408

PACKAGING LENGTH
580

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
35259360

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
5.5

PACKAGING NET WEIGHT
5.665

PACKAGING WEIGHT UNIT
KGM