

Downlight aluminium 735.20 NW Medium 1-10V

REF. 73520133-684



BASIC INFORMATION

DESCRIPTION

Downlight 735.20 with neutral colour temperature (4000 K) and 1-10 V control This luminaire is designed for general lighting technical and, therefore, is lead to create environments odours and uniform. Presents a high light output of 2500 lm / 24 W and, in addition, it is characterized by a high service life of 50,000 hours, always keep it in the appropriate conditions. The downlight is in aluminium colour and weight 1.3 kg It is suitable for flush mounting in ceiling. It is therefore recommended to do it in spaces whose temperature does not exceed the 35 ° C for a better conservation. This luminaire combines perfectly innovative design and visual comfort, resulting in an article perfect for your application in environments and restaurants or hospitals. In addition, it adapts to any decorative style, giving a touch modern, but with a minimum impact. It is a product that knows adapt to the tastes Aktualparameter.

APPLICATION

General technical lighting

PACKAGING CONTENTS

1 Unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

105 lm/W

IP RATING

IP20

ELECTRICAL CLASS

type 1

LUMENS (LM)

2500 lm

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

2500 lm/24W

POWER SUPPLY (V~)

220/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Medium

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

50,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

1-10 V

LIGHT BEAM APERTURE ANGLE (°)

65°

POWER (W)

24 W

CRI

80


COLOR TYPE

NW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Ceiling surface mount

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

150

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053136409

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.5

PRODUCT NET WEIGHT

1.2

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053136409

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

135

PACKAGING WIDTH

285

PACKAGING LENGTH

255

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

9811125

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.5

PACKAGING NET WEIGHT

1.2

PACKAGING WEIGHT UNIT

KGM