

Double Schuko socket outlet 16A 250V~ with safety device and quick terminal connection red K45

REF. K12/6



BASIC INFORMATION

FINISH

Red

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation on walls, floors, ceilings, and furniture, and Simon 500 Cima enclosures (requires combining with the K45 to 500 Cima adapter ref. 50012088-030).

ETIM CLASS

EC000125

TECHNICAL INFORMATION

FORMAT

Schuko

IP RATING

IP20

RAL

3002

CURRENT (A)

16 A

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

LOGISTICS INFORMATION

UNITARY EAN CODE 8421053354803	UNITARY PACKAGING GROSS WEIGHT 0.093	PACKAGING LENGTH 190
UNITARY PACKAGING HEIGHT 0	PRODUCT NET WEIGHT 0.085	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING WIDTH 0	UNITARY PACKAGING WEIGHT UNIT KGM	PACKAGING VOLUME 1653000
UNITARY PACKAGING LENGTH 0	PACKAGING EAN 8421053311592	PACKAGING VOLUME UNIT MMQ
UNITARY PACKAGING MEASUREMENT UNIT MMT	UNITS CONTAINED PACKAGING 6	PACKAGING GROSS WEIGHT 0.558
UNITARY PACKAGING VOLUME 0	PACKAGING HEIGHT 60	PACKAGING NET WEIGHT 0.51
UNITARY PACKAGING VOLUME UNIT MMQ	PACKAGING WIDTH 145	PACKAGING WEIGHT UNIT KGM