

Touch LightKeypad button box 8 functions (4 channels and 4 scenarios) graphite Simon Scena

REF. 89000152-038



BASIC INFORMATION

DESCRIPTION

Keypad touch LightKeypada 8 most off (4 channels and 4 scenes), finished in graphite colour and belonging to the series Simon Scena. We can program from Touch Light Manager channels, groups, scenarios, sequences. It is fed through a power 12 VDC -DMX and it has a signaling function. It also has IR input and compatible with the Simon 75350-69 remote control and complies with the European standards and regulations UNE -s 50491-3: 2010 + 2004 / 108 / CE + 2006 / 95 / EC. It can be position, place in places with a temperature of between 0 to 45°C, approximately, which makes it ideal for all types of climates and, for cleaning, just wipe it with a soft cloth and slightly moistened in soapy water, without resorting to never use cloths or abrasive cleaners containing chlorine, as they could damage it and make it does not operate the correct way.

FINISH

Graphite

PACKAGING CONTENTS

Touch LightKeypad, frame holder and instructions

ETIM CLASS

EC002466

COMPATIBILITY

Touch Light Manager

REMARKS

Fitted with an IR input and compatible with SIMON 75350-69 remote control.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

BASIC CHARACTERISTICS

8 actions and everything off, 4 channels and 4 scenes.

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM NUMBER OF CHANNELS

1

TYPE OF MECHANISM

Requires connection to Touch Light Manager, Touch pulse

OPERATING TEMPERATURE RANGE (°C)

0 - 45 °C

OPERATION

8 actions plus off

POWER SUPPLY (V~)

12 VDC/DMX

SIGNALLING FUNCTION

Yes

STORAGE TEMPERATURE RANGE (°C)

0 - 45 °C

USE

Short press for On/Off

INSTALLATION AND MAINTENANCE

BUS CONNECTION TYPE OF TERMINAL CONNECTION

Por inserción

CABLE CHARACTERISTICS DATA

Multicore AWG 24; 2 shielded twisted pairs with impedance of 120 Ohms

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Semi-flush mount; requires universal flush-mount box.

REGULATIONS

REGULATIONS

UNE-EN 50491-3:2010 + 2004/108/CE + 2006/95/CE

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053113011

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.114

PRODUCT NET WEIGHT

0.114

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053113011

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

35

PACKAGING WIDTH

120

PACKAGING LENGTH

105

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.441

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.114

PACKAGING WEIGHT UNIT

KGM