

USB 2.0 connector type B female with trim plate white Simon K45

REF. K131B/9



BASIC INFORMATION

DESCRIPTION

Type B USB 2.0 connector, female, that comes with a trim plate in white colour. It is a mechanism that has a female-female connection, a new much easier and fast, without welding. Included in the series Simon K45, is suitable for surface and flush mounting. It measures 22.5x45 mm and consists of a single module. It is manufactured with metal components with thermoplastic insulation and self-extinguishing halogen-free. This is a material that provides maximum security in case of fire, guaranteeing no flame spread in case of fire. The ideal is that the cabling does not exceed the 5 meters for low-speed devices such as keyboards, mice, or the 2,2 meters for those who are high-speed, such as the or the printers, hard drives. It is essential to the maintenance in this kind of parts. It will be enough to clean it with a soft and dry cloth.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Type B female USB 2.0 connector and instruction sheet

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 5 metres for low-speed devices (keyboards, mice) and 2.2 metres for high-speed devices (printers, hard drives, etc.) For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

FORMAT

USB

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

REVISION

+34 2.0

IP RATING

IP20

RAL

9003

CONNECTOR TYPE

USB

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1/2 element

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45
and specific Simon 500 Cima
using adaptor (ref.50012088-
030)

INSTALLATION TYPE

Suitable for surface and flush
mounting

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053112885

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053112885

PACKAGING VOLUME

0.001

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

50

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

40

PACKAGING NET WEIGHT

0.021

UNITARY PACKAGING GROSS
WEIGHT

0.021

PACKAGING LENGTH

50

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.021