

Voice and data flat plate with dust cover for 1 element and 1 RJ45 connector category 5e UTP aluminium Simon K45

REF. KA95U/8



BASIC INFORMATION

DESCRIPTION

Flat base plate of voice and data with dust cover with 1 element and 1 RJ45 connector of category 5e UTP in aluminium colour, the article measures 45x45 mm and has a depth of 30 mm is suitable for surface and flush mounting and contains metal parts with halogen-free thermoplastic material and self-extinguishing halogen-free. It is, therefore, a material 100% safe and guarantees the no-propagation of the flame in case of fire. The product is in compliance with the regulation and corresponds to the series Simon K45. This collection offers a wide variety of panels and connectors designed to facilitate the workplace solutions in all spaces. This voice and data plate can be combined in vertical enclosures and mini columns, columns, Teleblock. To do this, it would be necessary to use the 90° positioner (reference K66) to guide the plate vertically. In terms of maintenance, use a soft, dry cloth.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Voice and data flat plate with dust cover and RJ45 category 5e UTP connector

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

Four

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Flat

AVAILABLE IN

Plate with 1 and 2 RJ45 connectors

IP RATING

IP20

RJ45 ADAPTOR MODULE

Supplied with the voice and data plate

RJ45 CONNECTION

With insertion tool

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

CONNECTOR CHARACTERISTICS

Category 5e UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

VERSION

Single

MAX TEMP DURING

CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.017

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436046115

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

91140

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.175

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.17

UNITARY PACKAGING GROSS WEIGHT

0.017

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140