

T connector with LH exterior ground 3-phase rail Black

REF. 99911038-039



BASIC INFORMATION

APPLICATION

Domestic,Office,Retail,Contract

PACKAGING CONTENTS

1 Unit

ETIM CLASS

EC002556

TECHNICAL INFORMATION

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

CONTROL

On/Off

DRIVER INCLUDED

No

RAL

9005

DIRECTIONAL

No

ENERGY EFFICIENCY

A+

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Flush-mounted

INSTALLATION TYPE

Surface-mounted / Flush-mounted

REGULATIONS

EAC MARKED

No

ECORRAE MARKED

No

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8436547036998

PACKAGING VOLUME

0

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

0

PACKAGING GROSS WEIGHT

0.154

UNITARY PACKAGING GROSS
WEIGHT

0

PACKAGING WIDTH

0

PACKAGING NET WEIGHT

0.154

PRODUCT NET WEIGHT

0.154

PACKAGING LENGTH

0

PACKAGING WEIGHT UNIT

KGM