
IP66 Mechanism holder and manual frame with italian P40 socket and RJ45 6 UTP

REF. **KFH136U/72**



BASIC INFORMATION

DESCRIPTION

Simon completely renews its range of waterproof floor boxes for indoor and outdoor environments. This is a manual closure mechanism frame with an Italian P40 electrical base and a category 6 UTP RJ45 connector. In combination with its tub, it allows for installation on raised floors or pavement. The product design, combined with its stainless steel construction, achieves a robust, solid, and secure installation as it can withstand a water jet of 1 kg/cm^2 from any direction, reaching an IP66 protection rating when the lid is closed. It also supports a maximum load of 1500 kg and has an IK08 impact resistance. It maintains an optimal cable bend radius for high-category voice and data connections. Our accessory for connection with a closed lid is available, allowing us to keep our connections active with an IP54 (see reference KFA1001), the ability to level our box in case of uneven flooring (see reference KFA1003), or the capacity to concatenate more than one box (see reference KFA1002).

FINISH

Steel

COMPATIBILITY

K45 Solutions

MATERIAL

Polycarbonate

ETIM CLASS

EC000024

REMARKS

To complete the installation of the product, it must be combined with a tray for the IP66 waterproof floor box.

TECHNICAL INFORMATION

FORMAT

Italian

IP RATING

IP66

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

IK CLASSIFICATION

08

KIT AVAILABILITY

Yes

CURRENT (A)

16 A

MAXIMUM LOAD (KG)

1500 Kg - Closed box | 250 Kg - Open box

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

NUMBER OF COVER OPENING POSITIONS
1

EXTINGUISHING (ºC)
+650 ºC (according to standard IEC 60670)

REMOVAL OF THE FRAME
Only with tool

REMOVAL OF THE SOCKET
Only with tool

REGULATIONS

REGULATIONS
Dir. 2014/35/UE LVD|Dir. 2011/65/UE RoHS + post. mod.|EN 50173-1:2018 |EN 60670-23:2008 |EN IEC 63000:2018 |IEC 60884-1 Ed 3.2|CEI 23-50 V4

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053333082

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0

PRODUCT NET WEIGHT
0.384

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053333082

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
114

PACKAGING WIDTH
124

PACKAGING LENGTH
130

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1837680

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.462

PACKAGING NET WEIGHT
0.384

PACKAGING WEIGHT UNIT
KGM