

PD-20x3 Hallway HF+LUX recessed box DALI-2 Input white IP20

REF. 89215325-230



BASIC INFORMATION

DESCRIPTION

Flush-mounted presence and brightness detector HF. The recommended installation height is 2.8 m, with a maximum height of 3 m. It has a detection angle of 360 ° and an opening angle of 140 °. The tangential detection range is 20 x 3 m and the radial detection range is 20 x 3 m.

The brightness adjustment range is 10 - 1000 lux. The detector configuration is done via DALI.

Possibility of interconnection between sensors through DALI. The control protocol is DALI-2 Input. The typical consumption is 10 mA.

The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: -25 - 55 °C.

White finish, protection degree IP 20 and dimensions: 120 x 120 x 55 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9010

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053357743

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.29

PRODUCT NET WEIGHT

0.178

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053357743

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

142

PACKAGING LENGTH

100

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.29

PACKAGING NET WEIGHT

0.178

PACKAGING WEIGHT UNIT

KGM